

DASHCAM ACCESSORY

BD2000HUB

FleetCam Pro Hub — Channel Expansion Module

Get even more from your FleetCam Pro with the FleetCam Pro Hub. Improve visibility, safety, and driver accountability with up to six separate cameras capturing HD footage from around your vehicle. Support for AI-driven pedestrian detection alerts your driver to potential hazards, while an in-cab LCD provides a clear view for cargo monitoring or backing up.



Up to 6 Channels

OBD II & JBUS Plug & Play

iButton Driver ID

AI Pedestrian Alert

KEY FEATURES

- ✓ Plug & Play installation (OBD II & JBUS)
- ✓ Supports iButton for driver ID
- ✓ Built-in pedestrian warning alert
- ✓ Expands the FleetCam Pro to up to 6 channels
- ✓ HD footage captured from all around the vehicle
- ✓ In-cab LCD support for cargo & backing monitoring
- ✓ AI-driven pedestrian detection alerts drivers to hazards
- ✓ Improves visibility, safety, and driver accountability

APPLICATIONS

Multi-Camera Fleet Visibility

Cargo & Backing Monitoring

Driver ID via iButton

Pedestrian Safety Alerts

BD2000HUB — Full Technical Specifications

POWER

Power Supply	DC 9-36V
Output	12V @ 2A
Standby	24V @ 5mA

VIDEO

Input	4 ch. AHD -or- 3 ch. AHD + 1 ch. IPC
Output	1 ch. video output, configurable as AHD or CVBS output

PHYSICAL

Size	192 × 57 × 30 mm
Weight	554g (Bare Metal)

PORT

RS232	3 ch. (232-1 connects to V-Display by default, 232-2 connects to left side of B3, 232-3 connects to right side of B3)
Sensor In/Out	3 Inputs / 1 Output
iButton	1 channel
USB	1× USB 2.0 (Type A), used for local upgrade
LAN	1 ch., connects to FleetCam Pro

ENVIRONMENT

Operating Temp.	-40°C ~ +70°C
Storage Temp.	-40°C ~ +85°C
Working Humidity	15%-95% (no condensation)

AT A GLANCE

Up to 6 Camera Channels

OBD II & JBUS Plug & Play

iButton Driver ID

AI Pedestrian Alert

In-Cab LCD Support

“Expand any FleetCam Pro system to six camera channels, with plug-and-play OBD II / JBUS installation, iButton driver ID, and AI pedestrian alerts built in.”